



ARTROMOT®-SP3 COMFORT CHIP

for the ankle joint

Technical Data:

Models

ARTROMOT®-SP3 STANDARD

ARTROMOT®-SP3 STANDARD CHIP

ARTROMOT®-SP3 COMFORT

ARTROMOT®-SP3 COMFORT CHIP

Range of motion

Plantar flexion / Dorsal extension 50° / 0° / 40°

Inversion / Eversion 40° / 0° / 20°

Functions of ARTROMOT®-SP3 STANDARD

Timer 1 – 59 minutes / 1 – 24 hours / continuous operation

Pauses 0 – 59 seconds

Speed 5 % – 100 %

Reverse on load in steps (motor A and B separately) 1 – 25 / patient safety feature

Motor control ON/OFF for isolated motion, plantar flexion/dorsal extension or inversion/eversion

Synchronized motors ON/OFF

Total therapy time added sum of the therapy sessions

New patient activates the default settings for new patients

Transport setting moves the motors into the transport position

Key lock function prevents accidental changes of the parameter settings

Service menu

Additional functions of ARTROMOT®-SP3 COMFORT

Stretching modes for gradual and smooth increase of the range of motion

Therapy documentation graphic presentation of the overall treatment cycle

Warm-up protocol gradual progression to the maximum range of motion

ISO protocol for separate exercising in both directions

Additional functions of ARTROMOT®-SP3 models with Chip card

Patient chip card stores patient-specific therapy parameters

Physical

Weight 11 Kg (24.4 lb)

Dimensions 78 x 42 x 39,5 cm (30.7 x 16.5 x 15.5 in)

Patient height approx. 120 – 200 cm (47.2 – 78.8 in)

Article numbers:

ARTROMOT®-SP3 STANDARD 80.00.035

ARTROMOT®-SP3 STANDARD CHIP 80.00.036

ARTROMOT®-SP3 COMFORT 80.00.037

ARTROMOT®-SP3 COMFORT CHIP 80.00.038

Transport trolley 80.00.056